



10.09.2016



2018. 8. 10





10.09.2016



ASUS


S/N: C90KGT183430

10.09.2016





15.09.2016

Seagate 

Barracuda ES.2  
500 Gbytes

S/N: 50M18G5D

ST3500320NS

P/N: 9CA154-302

Firmware: SN04

Date Code: 08375 Site Code: WUXISG

WWN: 5000C5000B65700

Caution: Product warranty is void if any seal or label is removed, or if the drive experiences shock in excess of 300 Gs.



+5V 0.65A  
+12V 0.42A

中国产品  
Product of China



STX-ST3500320NS (B)

This drive is manufactured by Seagate for OEM distribution. For product information or technical support, please contact your system OEM.





Installation Summary

For easy installation use Seagate's DiscWizard™ software, available at [www.seagate.com/discwizard](http://www.seagate.com/discwizard)

1. Connect cables. The data interface and power cables are tested.  
2. Attach the drive using the screws provided. Do not over-tighten.  
3. Connect the drive to the system. Do not connect the drive to the system until the drive is fully initialized.  
4. Prepare the system to connect the system drive. Always backup critical data before connecting the drive. Do not connect the drive to the system until the drive is fully initialized.  
Power: Data  
SATA  
SATA  
SATA  
SATA

Limit to 1.2 Gbit/s Operation  
3 Gbit/s Operation



Seagate 

Barracuda ES.2  
500 Gbytes

S/N: 50M1A94N

ST3500320NS

P/N: 9CA154-302

Firmware: SN04

Date Code: 08375 Site Code: WUXISG

WWN: 5000C5000B65700

Caution: Product warranty is void if any seal or label is removed, or if the drive experiences shock in excess of 300 Gs.



+5V 0.65A  
+12V 0.42A

中国产品  
Product of China



STX-ST3500320NS (B)

This drive is manufactured by Seagate for OEM distribution. For product information or technical support, please contact your system OEM.




Installation Summary

For easy installation use Seagate's DiscWizard™ software, available at [www.seagate.com/discwizard](http://www.seagate.com/discwizard)

1. Connect cables. The data interface and power cables are tested.  
2. Attach the drive using the screws provided. Do not over-tighten.  
3. Connect the drive to the system. Do not connect the drive to the system until the drive is fully initialized.  
4. Prepare the system to connect the system drive. Always backup critical data before connecting the drive. Do not connect the drive to the system until the drive is fully initialized.

ХУД, ФИЛЬМЫ  
УТЕХНЫЕ  
А. И. ШИШКИН  
Google Video

Limit to 1.2 Gbit/s Operation  
3 Gbit/s Operation



14.09.2016